

Wall Fan (배기팬-Fiber)

농축산 전용 배기팬으로서, 특히 축산시설(우사, 돈사, 계사)에서 발생하는 암모니아로 인한 금속부품의 부식을 방지하기 위해 화이버(FRP)소재로 완성.

Fibreglass Exhaust Fans



FRP with cone ,
high strength ventilation,
attractive and durable

Low Noise ,
High Quality Nylon Fan Blade ,
Easy Installation ,
High Strength Aluminum Alloy



The fan blade was made
by cast aluminum,
Large air flow,
no deformation,
no fracture,
no dust,
attractive appearance
and durable



Large Air Volume ,
Anti corrosion ,
High Speed Ventilation



1. High strength aluminum-alloy by die-casting.
2. Blast-sanding treatment, eliminate internal stress to improve its own rigidity and stability
3. Attractive appearance



(주)빅팬테크
조달청 등록업체
국내생산 및 설치 컨설팅

Air - control

공장 및 물류센터의 온/습도 관리 컨설팅,
연락 주시면 현장방문하여
최적의 솔루션을 제안 드리겠습니다.

문의 : 1599 - 9370

Wall Fan (배기팬-Fiber)

축산시설에서 발생하는 암모니아 가스로 인한 금속부품의 부식을 방지하기 위해 FRP소재로 보완한 제품입니다.



각 제품 모델별 능력

1460 * 1460 * 580mm : 45,000(m3/h) / 750(m3/min) / 26,500 CFM
 1260 * 1260 * 560mm : 37,000(m3/h) / 620(m3/min) / 22,000 CFM
 1460 * 1460 * 550mm : 32,000(m3/h) / 533(m3/min) / 19,000 CFM
 1460 * 1460 * 480mm : 28,000(m3/h) / 467(m3/min) / 16,500 CFM

Technical Specifications							
Model	Dimensions (WxHxD)	Input Voltage	Speed (min/max)	Max Air Volume (CFM)	Power	Sound level	Net Weight(kg)
Exhaust Fan F146#	1460*1460*580	220 VAC, 1 phase, 60Hz	560 rpm	26,500	1.1kw	65 dB	65
Exhaust Fan F126#	1260*1260*560		560 rpm	22,000	0.75 kw	65 dB	55
Exhaust Fan F106#	1060*1060*550		560 rpm	19,000	0.55 kw	55 dB	45
Exhaust Fan F85#	850*850*480		620 rpm	16,500	0.37 kw	53 dB	35

Construction Features					
Airfoils	Motor	Certifications	Controler	HMI	Other Hardware
FRP	100% full copper, IP54 F Insulation	 Korea Certification	Direct Type	No	FRP, 1.0mm / 0.35mm

